



# MASTER PL-C 4 Pin



## MASTER PL-C 26W/830/4P 1CT/5X10BOX

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data


General Information		Color rendering index (CRI)	
Cap-Base	G24q-3		81
Flux measurement reference	Sphere	Operating and Electrical	
Light Technical		Power Consumption	27.4 W
Color Code	830 [CCT of 3000K]	Lamp Current (Nom)	0.335 A
Luminous Flux	1,800 lm	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	67 lm/W	Dimmable	Yes
Color Designation	Warm White (WW)	Approval and Application	
Chromaticity Coordinate X (Nom)	0.44	Energy Efficiency Class	G
Chromaticity Coordinate Y (Nom)	0.403	Mercury (Hg) Content (Max)	1.4 mg
Correlated Color Temperature (Nom)	3000 K	Mercury (Hg) Content (Nom)	1.4 mg

# MASTER PL-C 4 Pin

Energy Consumption kWh/1000 h	28 kWh
EPREL Registration Number	423305
<b>Product Data</b>	
Order product name	MASTER PL-C 26W/830/4P 1CT/5X10BOX
Full product name	MASTER PL-C 26W/830/4P 1CT/5X10BOX
Full product code	871150062335570
Order code	927907383040


Material Nr. (12NC)	927907383040
Numerator - Quantity Per Pack	1
Net Weight (Piece)	60.400 g
EAN/UPC - Product/Case	8711500623355
Numerator - Packs per outer box	50
EAN/UPC - Case	8711500716040

## Dimensional drawing



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 26W/830/4P 1CT/ 5X10BOX	27.1 mm	27.1 mm	130.5 mm	149.0 mm	163.9 mm

## Photometric data



Spectral Power Distribution Colour - MASTER PL-C 26W/830/4P 1CT/5X10BOX


# MASTER PL-C 4 Pin

## Lifetime



Life expectancy diagram - 3 hour cycle

Life expectancy diagram - 12 hour cycle



Lumen Maintenance Diagram - MASTER PL-C 26W/830/4P 1CT/5X10BOX

